



Overall inner and outer ring

(Unit) : mm

Model	Dimensions						Basic rated load		Weight	Corresponding model
	Inner ring	Outer ring	Width	Pitch diameter	Shoulder height		Radial direction			
	d	D	B	Dpw	ds	Dh	C	Co	Kg	IKO
JRBS5008	50	66	8	57	53.5	60.5	5.1	7.19	0.08	CRBS508
JRBS6008	60	76	8	67	63.5	70.5	5.68	8.68	0.09	CRBS608
JRBS7008	70	86	8	77	73.5	80.5	5.98	9.8	0.1	CRBS708
JRBS8008	80	96	8	87	83.5	90.5	6.37	11.3	0.11	CRBS808
JRBS9008	90	106	8	97	93.5	100.5	6.67	12.4	0.12	CRBS908
JRBS10008	100	116	8	107	103.5	110.5	7.15	13.9	0.16	CRBS1008
JRBS11008	110	126	8	117	113.5	120.5	7.45	15	0.15	CRBS1108
JRBS12008	120	136	8	127	123.5	130.5	7.84	16.5	0.17	CRBS1208
JRBS13008	130	146	8	137	133.5	140.5	7.94	17.6	0.18	CRBS1308
JRBS14008	140	156	8	147	143.5	150.5	8.33	19.1	0.19	CRBS1408
JRBS15008	150	166	8	157	153.5	160.5	8.82	20.6	0.2	CRBS1508
JRBS16013	160	186	13	172	165	179	23.3	44.9	0.59	CRBS1613
JRBS17013	170	196	13	182	175	189	23.5	46.5	0.64	CRBS1713
JRBS18013	180	206	13	192	185	199	24.5	49.8	0.68	CRBS1813
JRBS19013	190	216	13	202	195	209	24.9	51.5	0.69	CRBS1913
JRBS20013	200	226	13	212	205	219	25.8	54.7	0.71	CRBS2013